


**NOTES:**

1. Display size: 11" TN TFT
2. Viewing direction: 6 O'Clock  
Gray scale inversion direction: 12 O'Clock
3. Display mode: Transmissive/Normal white
4. Operation temperature: -10°C~+60°C  
Storage temperature: -20°C~+70°C
5. Driver IC: HX8290-A02 and HX8678-C01
6. Power supply voltage: 3.3V
7. Backlight : White/27 LEDs/If: 180 mA;  
Vf: 9.0~9.6V(typ)~10.5; Luminance: 900 cd/m<sup>2</sup>(TYP)
8. FPC mating connector: Molex 52271-3069 or equivalent
9. RoHS compliant
10. General Tolerance are ±0.2mm



LED CIRCUIT  
3\*9=27 LEDs, 20mA\*9=180mA

PIN FUNCTION	
PIN	SYMBOL
1	VDD
2	VDD
3	B0
4	B1
5	B2
6	B3
7	B4
8	B5
9	VSS
10	G0
11	G1
12	G2
13	G3
14	G4
15	G5
16	VSS
17	R0
18	R1
19	R2
20	R3
21	R4
22	R5
23	VSS
24	DCLK
25	VSS
26	HSYNC
27	VSYNC
28	DEN
29	LEDK
30	LEDA

**LOGIC TECHNOLOGIES**

Part Number	Revision
LTTD1280120110-L2-HB	A
Not to scale. Unit mm.	
Sheet: 1/1	